ELEVATION CERTIFICAT FEL_AL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. No. 3067-0077 Expires July 31, 1999

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodpain analogement ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Recision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form. Instructions for completing this form can be found on the following pages.

	. (2Y MAY 1007		•
SECTION A PROPERTY INFORMATION	A PEOCOUT	FORINSUF	RANCE COMPANY USE
BUILDING OWNER'S NAME	INSPECTION	POLICY NL	IMBER
Michael & Marie Kilroy	12		
STREET ADDRESS (Including Apt., Unit, Suite and or Bldg. Number) OR P.O. ROUTE AND BOX	NUMBER	COMPANY	NAIC NUMBER
925 Arawak Avenue	No.	or	
OTHER DESCRIPTION (Lot and Block Numbers, etc.)	2018820	in the second	
Lot 4, Block 175 Marco Beach Unit 7			
CITY	STATE		ZIP CODE
Marco Island		FL	34145
SECTION B FLOOD INSURANCE RATE M	AP (FIRM) INFORMATI	ON	

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
120067	0812	Е	2-16-95	AE	+11.00'

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): 🖾 NGVD '29 🗍 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate

the community's BFE: _______ feet NGVD (or other FIRM datum-see Section B, Item 7)

SECTION C BUILDING ELEVATION INFORMATION

- 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level <u>1</u>.
- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of <u>111,0</u> feet NGVD (or other FIRM datum-see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is ______ feet above _____ or below _____ (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is ______ feet above _____ or below _____ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? ____ Yes ___ No ____ Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 _____ Other`(describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: $\underline{\overline{x}}$ Yes $\underline{\overline{x}}$ No (See Instructions on Page 4)
- 5. The reference level elevation is based on: X actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: <u>7.2</u> feet NGVD or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

 If the community official responsible for verify 	ing building elevations specifies that the reference level indicated in Section C. Item *
is not the "lowest floor" as defined in the corn	munity's floodplain management ordinance, the elevation of the building's "lowest
floor" as defined by the ordinance is:	feet NGVD (or other FIRM datum-see Section E. Item 7).
2. Date of the start of construction or substantia	Limprovement

2. Date of the start of construction or substantial improvement

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information to Zones A1–A30, AE, AH, A (with BFE).V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment; area use; wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number. Section C. Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NI IMBER (or Affire Sool)			
Antonio Trigo	2002			
TITLE				
Professional Surveyor &	Mapper A. Trigo & Associates.	Inc.		
2223 Trade Center Way	CITY STATE	ZIP		
SIGNATURE	May 20, 1997 (941)594-844	<u>34109</u> 8		
Copies should be made of this Certificate fo	pr: 1) community official, 2) insurance agent/company, and 3) bui	ding owner.		
COMMENTS:				



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.