97081016

ESEE REVERSE SIDE FOR CONTINUATION

ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. No. 3067-0077 Expires July 31, 1999

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION FOR INSURANCE COMPANY USE BUILDING OWNER'S NAME POLICY NUMBER Rosemary Rodriguez STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER COMPANY NAIC NUMBER 1310 Auburndale Avenue OTHER DESCRIPTION (Lot and Block Numbers, etc.) Lot 3, Block 295, MARCO BEACH UNIT EIGHT STATE ZIP CODE CITY 34145 Marco Island SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 6. BASE FLOOD ELEVATION (in AO Zones, use depth) 2. PANEL NUMBER 3. SUFFIX 4. DATE OF FIRM INDEX 5. FIRM ZONE 1. COMMUNITY NUMBER 10' E 8-3-92 AE 120067 0812 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): XNGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: Label Label I feet NGVD (or other FIRM datum-see Section B, Item 7). SECTION C BUILDING ELEVATION INFORMATION 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level ______. 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 10/2 feet NGVD (or other FIRM datum-see Section B, Item 7). (b), FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of the selected diagram and the selected diagram and the selected diagram. (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is ______ feet above ____ or below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is _______ feet above ___ or below ___ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? ___ Yes __ No __ Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Yes X No (See Instructions on Page 4) 5. The reference level elevation is based on: [X] actual construction [1] construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: Section B. Item 7). SECTION D COMMUNITY INFORMATION 1. If the community official responsible for verifying building elevations specifies that the eleven the building's "lowest is not the "lowest floor" as defined in the community's floodplain management ordinance, the e floor" as defined by the ordinance is: 2. Date of the start of construction or substantial improvement

REPLACES ALL PREVIOUS EDITIONS

FEMA Form 81-31, AUG 96

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

4920

ADJACE:

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

Scott E. Marhenke

CERTIFIER'S NAME

P.S.M.	OMNI SURVEYS, INC.		
4568 Alton Court ADDRESS Lott E. Malanto	COMPANY NAME Fort Myers,	FL	33907
	CITY 11-6-97	(941) 939-3666 STATE	ZIP
SIGNATURE	DATE	PHONE	- Branchistan (1997)
Copies should be made of this Certificate	for: 1) community official, 2) insuran	ce agent/company, and 3) buildin	g owner.
COMMENTS:			
			A Company of the Comp
	70 managa ar a a 2,747 ar as ag as 7,147 ar and a		
and the second s			
ON SLAB	WITH BASEMENT	ON PILES, PIERS, OR COLUMNS	
A V ZONES ZUNES	Mr zones	A V ZONES ZONES TA	
REFERENCE IN THE	HASE	HEFERENCE	EFERENÇE
	FLOOD ELEVATION		LEVEL
the second second		mp)	~~~

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

AUJACENT

Elevations for all Zones should be measured at the bottom of the lowest horizontal structural member.

ALUACENT

HEFERENCE