1 4540

# **ELEVATION CERTIFICATE** FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form. Instructions for completing this form can be found on the following pages.

	SECTION A PRO	PERTY INFO	RMATION		FOR INSURANCE COMPANY USE	
JILDING OWNER'S NAME	POLICY NUMBER					
Paul E. Uqle STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg, Number) OR P.O. ROUTE AND BOX NUMBER					COMPANY NAIC NUMBER	
875 Cascade Co		••••••••••••••••••••••••••••••••••••••				
		ach Unit	2			
ot 18, Block 5	55. Marco Dec		·	STATE	ZIP CODE	
ITY T T T T				FI	34145	
larco Island			NCE RATE MAP (FIRM)	INFORMATION	J	
ovide the following from the	he proper FIRM (See	Instructions):				
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)	
	0804	D	7/20/98	AE	+10.0'	

the community's BFE: \_\_\_\_\_ feet NGVD (or other FIRM datum-see Section

### SO SECTION C BUILDING ELEVATION INFORMATION

- 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level  $\_1$  .
- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 10.2 feet NGVD (or other FIRM datum-see Section B, Item 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of \_\_\_\_\_\_ feet NGVD (or other FIRM datum-see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is \_\_\_\_\_\_ feet above \_\_\_\_\_ or below (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is \_\_\_\_\_. \_\_\_ feet above \_\_\_\_\_ or below \_\_\_\_\_ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? \_\_\_\_ Yes \_\_\_ No \_\_\_ Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations: 🛣 NGVD '29 🗌 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: Types X No (See Instructions on Page 4)
- 5. The reference level elevation is based on:  $\overline{\mathbf{x}}$  actual construction  $\Box$  construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: \_\_\_\_\_7.1\_ feet NGVD (or other FIRM datum-see Section B, Item 7).

## SECTION D COMMUNITY INFORMATION

- 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest
- floor" as defined by the ordinance is: \_\_\_\_\_\_\_ feet NGVD (or other FIRM datum-see Section B, Item 7).

## SECTION E CERTIFICATION


This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE. and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

1. 1. 1.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seal)								
Antonio Trigo		,	2982						
TITLE	COMPANY NAME								
Professional Surveyor &	Mapper	A. Tr	igo 8	Assoc	iates,	Inc.			
ADDRESS	CITY					STATE	ZIP		
2223 Trade Center Way	Naples					FL	34109		
SIGNATURE		Anni	DATE	2000	PHONE (941)	594-8448			
Copies should be made of this Certificate for	: 1) community offi	cial, 2) in	surance	agent/com	npany, and	3) building ow	ner.		
Copies should be made of this Certificate for COMMENTS:	: 1) community offi	cial, 2) in	surance	agent/com	ipany, and	3) building ow	ner.		
	: 1) community offi	cial, 2) in	surance	agent/com	ipany, and	3) building ow	ner.		



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.