EVATION CERTIFICAT FEDE EMERGENCY MANAGEMENT FNCV NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions	for completing	this form	can be	found c	on the fo	Howing	pages.	
monaonono	or completing		can be	iouna c	on the to	nowing	pages.	

			s ionn can be iound or	the following pa	iges.
	SECTION A PRO	PERTY INFO	ORMATION	12 2	OR INSURANCE COMPANY USE
BUILDING OWNER'S NAME ERNST E STREET ADDRESS (Including A 520 F	pt., Unit, Spite and/or Bldg. N	KOESS lumber) OR P.O. I	ROUTE AND BOX NUMBER	CHANGTET	OLICY NUMBER
OTHER DESCRIPTION (Lot and LOT 10, B1	Block Numbers, etc.)	, Mar	co Beach	Unit	Seven
Marco =	Island.			FIDRide	ZIP CODE
	SECTION B FL	OOD INSURA	NCE RATE MAP (FIRM)	INFORMATION	
Provide the following from t	he proper FIRM (See I	nstructions):			
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION
120067	0812	E	8-3-92	AE	(In AO Zones, use depth)
8. For Zones A or V, where the community's BFE:	no BFE is provided on	the FIRM, an GVD (or other	rid the community has esti FIRM datum-see Section	ablished a BFE for	this building site, indicate
	SECTIO	NC BUILDI	NG ELEVATION INFORM	IATION	
 Using the Elevation Certi describes the subject bu FIRM Zones A1-A30, <i>J</i> of L L I I J. B fee (b). FIRM Zones V1-V30, ^V the selected diagram, i (c). FIRM Zone A (without below □ (check one) 	ficate Instructions, indi ilding's reference level AE, AH, and A (with BF et NGVD (or other FIRM VE, and V (with BFE). 's at an elevation of BFE). The floor used the highest grade adja	cate the diagr FE). The top of datum-sees The bottom o datum-sees the referen	am number from the diag of the reference level floo Section B, Item 7). f the lowest horizontal str feet NGVD (or other FIR ce level from the selected uilding.	rams found on Pa r from the selected uctural member of M datum-see Sec d diagram is	ges 5 and 6 that best diagram is at an elevation the reference level from tion B, Item 7).
(d). FIRM Zone AO. The fi one) the highest grade level) elevated in accor	loor used as the refere adjacent to the buildin rdance with the commu	nce level from g. If no flood inity's floodpla	n the selected diagram is depth number is available ain management ordinanc	│	ove [] or below ^[] (check lowest floor (reference o [] Unknown
3. Indicate the elevation data under Comments on Page the FIRM [see Section E	um system used in det e 2). <i>(NOTE: If the ele</i> 3, <i>Item 7], then convert</i>	ermining the a evation datum the elevation	above reference level elevel used in measuring the elevel of the datum system us	vations: KNGVD levations is difference and on the FIBM au	'29 Other (describe) In than that used on) ad show the conversion)

equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Yes KNo (See Instructions on Page 4)

5. The reference level elevation is based on: Kactual construction Construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place. In which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)

6. The elevation of the lowest grade immediately adjacent to the building is: 11117. C feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

1.	If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C. Item 1
	is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest
	floor" as defined by the ordinance is:
2.	Date of the start of construction or substantial improvement

Expires July 31, 1999

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

105

da.

Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number. Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

LICENSE NUMBER (or Affix Seal) CERTIFIER'S NAME P. Robinette 4944 and Surveyor & Pres. LB 5982 Josef Robinette & Eaton, Inc. RO Maples ADDRESS Ave. N.W. Florida HONE -0085

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

COMMENTS: Benchmark Base-Florida Dept. of Natural Resources Collier #26 1984 National Geodetic Vertical Datum of 1929 Building & Site Under Construction



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.