

ELEVATION CERTIFICATE
FEDERAL EMERGENCY MANAGEMENT AGENCY
NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. No 3067-0077
 Expires May 31, 1993

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION		FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME CATHY SLAWIK		POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER 721 PARTRIDGE COURT		COMPANY NAIC NUMBER

OTHER DESCRIPTION (Lot and Block Numbers, etc.)

SECTION 21 AND 28, TOWNSHIP 52 SOUTH, RANGE 26 EAST

CITY

STATE

ZIP CODE

MARCO ISLAND, FLORIDA

MB410, BL 327 lot 24

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
120067	0812	D	06/03/86	AE	11'

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back)

8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: _____ feet NGVD (or other FIRM datum—see Section B, Item 7).

SECTION C BUILDING ELEVATION INFORMATION

- Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level 1.
- (a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 12.35 feet NGVD (or other FIRM datum—see Section B, Item 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of 11.11 feet NGVD (or other FIRM datum—see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is 11.11 feet above or below (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is 11.11 feet above or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown
- Indicate the elevation datum system used in determining the above reference level elevations: NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM, [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- Elevation reference mark used appears on FIRM: Yes No (See Instructions on Page 4)
- The reference level elevation is based on: actual construction construction drawings
(NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- The elevation of the lowest grade immediately adjacent to the building is: 9.75 feet NGVD (or other FIRM datum—see Section B, Item 7).


SECTION D COMMUNITY INFORMATION

- If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: 11.11 feet NGVD (or other FIRM datum—see Section B, Item 7).
- Date of the start of construction or substantial improvement _____.

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.



COMMENTS:

Copies should be made of this Certificate for: 1) Community official, 2) insurance agent/company, and 3) building owner.

CERFIFER'S NAME: JOHN GENEVEND NO. P.I.S. #4085		COMPANY NAME: ACTION SURVEYS AND PLANNERS, INC.	
ADDRESS: 3400 RADIQ ROAD SUITE 111 NAPLES, FLORIDA 33942		STATE: FL	ZIP: 33942
PHONE: 813-643-7510		DATE: AUGUST 18, 1993	SIGNATURE: [Signature]

I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available.

Reference levels shown in diagrams 6, 7 and 8 - Distinguishing Features-if the certifier is unable to certify to breakaway/non-breakaway wall, enclosures size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

Comments when the elevation information for Zones A1-A30, AE, AH, A (With BFE), V1-V30, VE, and V (With BFE) is required. This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation certificates. In the case of Zones AO and A (Without a FEMA or community management issued BFE), a building official, a property owner, or an owner's representative may also sign the certification. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (Without a FEMA or community management issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.