

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

# 24 95 302574

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION
BUILDING OWNER'S NAME: Jack Ketterhoff (Foster Res.)
STREET ADDRESS: 811 Ferrine Court
CITY: Marco Island, FL
STATE: FL
ZIP CODE: 34145

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM (See instructions):

Table with 6 columns: 1. COMMUNITY NUMBER (120067), 2. PANEL NUMBER (0803), 3. SUFFIX (B), 4. DATE OF FIRM INDEX (8-3-92), 5. FIRM ZONE (AE), 6. BASE FLOOD ELEVATION (11.0')

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): [ ] NGVD '29 [ ] Other (describe on back)
8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: [ ] feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION C BUILDING ELEVATION INFORMATION

- 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level.
2(a). FIRM Zones A1-A30, AE, AM, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of [ ] feet NGVD (or other FIRM datum-see Section B, Item 7).
(b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram is at an elevation of [ ] feet NGVD (or other FIRM datum-see Section B, Item 7).
(c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is [ ] feet above [ ] or below [ ] (check one) the highest grade adjacent to the building.
(d). FIRM Zone AO. The floor used as the reference level from the selected diagram is [ ] feet above [ ] or below [ ] (check one) the highest grade adjacent to the building.
3. Indicate the elevation datum system used in determining the above reference level elevations: [ ] NGVD '29 [ ] Other (describe under Comments on Page 2).
4. Elevation reference mark used appears on FIRM: [X] Yes [ ] No
5. The reference level elevation is based on: [X] actual construction [ ] construction drawings
6. The elevation of the lowest grade immediately adjacent to the building is: [ ] feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: [ ] feet NGVD (or other FIRM datum-see Section B, Item 7).
Date of the start of construction or substantial improvement: [ ]

Permit 12-4737

#2495302574

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features--If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME: Martin D. Pinckney, P.E. LICENSE NUMBER (or Affn Seal): 338350


TITLE: Branch Manager COMPANY NAME: American Engineering Consultants, Inc.

ADDRESS: 573 Bald Eagle Drive CITY: Marco Island STATE: FL ZIP: 36145

SIGNATURE: [Signature] DATE: July 18, 1996 PHONE: 394-1697

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

COMMENTS:



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor. Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.