96-14171

ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM ATTENTION (Wise of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to pro-

wide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine

O.M.B. No. 3067-0077

Expires July 31, 1999

SEE REVERSE SIDE FOR CONTINUA

The proper in a large premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not world to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form. Instructions for completing this form can be found on the following pages. SECTION A PROPERTY INFORMATION FOR INSURANCE COMPANY USE POLICY NUMBER STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER COMPANY NAIC NUMBER S.R. #92 - San Marco Drive OTHER DESCRIPTION (Lot and Block Numbers, etc.) Block 70, Marco Beach, Unit 2 ZIP CODE STATE CITY Florida Island, Marco SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 5. FIRM ZONE 6. BASE FLOOD ELEVATION 3. SUFFIX 4. DATE OF FIRM INDEX . COMMUNITY NUMBER 2. PANEL NUMBER (in AO Zones, use depth) +10.0' 2-16-95 AE 0812 120067 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): 🗵 NGVD '29 🔲 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: ______ feet NGVD (or other FIRM datum-see Section B, Item 7). BUILDING ELEVATION INFORMATION SECTION C 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level 1. 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation 10.5 feet NGVD (or other FIRM datum-see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of _______ feet NGVD (or other FIRM datum-see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is _____. feet above ____ or below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is 📖 feet above 🗌 or below 🔲 (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? 🔲 Yes 🔲 No 🛄 Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: 🗵 NGVD '29 🔲 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: ___ Yes x No (See Instructions on Page 4) 5. The reference level elevation is based on: 🗵 actual construction 🔲 construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 9.7 feet NGVD (or other FIRM datum-see 6. The elevation of the lowest grade immediately adjacent to the building is: Section B, Item 7). COMMUNITY INFORMATION SECTION D 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest

floor" as defined by the ordinance is: ______ feet NGVD (or other FIRM datum-see Section B, Item 7).

REPLACES ALL PREVIOUS EDITIONS

2. Date of the start of construction or substantial improvement

FEMA Form 81-31, AUG 96


SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

| CERTIFIER'S NAME | LICENSE NUMBER (or Affix Seal) |
|---|--|
| Antonio Trigo | 2982 |
| TITLE | NY NAME |
| Professional Surveyors & Mappers | A. Trigo & Associates, Inc. |
| ADDRESS | STATE ZIP |
| 223 Trade Center Way | Naples, Florida 34109 |
| SIGNATURE | DATE PHONE (941) 594-84 |
| Copies should be made of this Certificate for: 1) community | official, 2) insurance agent/company, and 3) building owner. |
| COMMENTS/ | |
| | |



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.